

KNEBEL DRILLING A/S



HY - 96 - GRS - C

KNEBEL DRILLING A/S type HY - 96 - GRS - C, diesel hydraulic, 6 inch, compact investigation drill rig is unique in its design, size, capacity and stability.

This small rig can use 1.500 mm long drill rod, with a maximum torque at the Rotary Head up to 3.000 Nm, a maximum bore through the axle at $\varnothing 232$ mm assure handling of 6 inch casing as a casing rotator during wire-line percussion drilling.

Drilling capacity 30 metre 6 inch with casing. The drill rig is self propelled in the field, type of carriage: Rubber band Caterpillar, maximum weight 1750 kg.



Total Width minimum	700 mm
Total width maximum	1.000 mm
Total height transport	1.670 mm
Total length transport	2.920 mm
Height operation min.	2.250 mm
Height operation max.	3.050 mm
Mast height displacement	600 mm
Clamp height displacement	300 mm
Stroke at Rotary Head	1.800 mm
Hold back capacity	30.000 N
Pull down capacity max.	15.000 N
Winch line pull max.	12.000 N
Free fall percussion automatic on winch	



KNEBEL DRILLING A/S
INDUSTRIVEJ 20
DK-8550 RYOMGÅRD
E-mail

TELEPHONE: +45 86 39 45 00
FAX: +45 86 39 47 20
GIRO: 5 09 26 20
Knebeldrilling@knebeldrilling.dk

A/S REG. NR. 63479
SE DK 83089113
SE EXPORT DK 15 22 80 40