

KNEBEL DRILLING A/S



HY-102-BRS, Truck Mounted Drill Rig!

KNEBEL DRILLING A/S type HY-102-BRS, Truck mounted drill rig, is a PTO driven, heavy duty water well rig, with capacity to drill with direct mud / air circulation, reverse Mud / air circulation and wire-line percussion, We hereby have the pleasure to offer the following Truck mounted drilling equipment, designed for drilling water well to a depth of more than 700 m with 7 7/8" or 500 m with 9 7/8" three cone rock roller bit tool using mud flushing. DTH hammer drilling, is with air foam and water injection. Max. hole diameter 20 inch, max. drilling depth 1.000 meter hole Recommended weight of max. in hole tools 26 metric ton.

The design of the drilling rig is unique in it easy way to carrier and handle drilling tools, in fact it is only a one man operation.



Dimension of rig during transport:

Total width of rig	2.550 mm
Total length of rig incl. Mast	11.300 mm
Total height of rig	3.950 mm
Total weight empty, 6 x 6 truck incl.	24.100 kg

Technical rig Specification:

Standard power input at hydraulic system	180 kW
Hold back / pull down	400 kN / 210 kN
Rotary head, working stroke	7.600 mm
Rotary head, travel-speed up and down	36 m / min
Rotary head max. torque 1 st . gear	13.500 Nm
Rotary head max. torque 2 nd . gear	7.000 Nm
Rotary head speed 1 st . gear	2 to 65 RPM
Rotary head speed 2 nd . Gear	2 to 130 RPM
Rotary head tip	2 x 90°
Winch with free fall, max. line pull	30 kN
Line speed	0 to 65 m /min
Numbers of stroke / min. for percussion	32 to 48
Length of stroke adjustable from	0,2 to 1,0 meter
Hydraulic bottom clamp	ø 419/559 mm
Hydraulic bottom clamp load capacity	400 kN
Jib boom for Rod handling	10 kN, 360° swing
Break-O-Matic for easy breaking of threads	7.500 Nm
Hydraulic chuck for locking rotary head to drill pipe.	
Night light, remote control, compressor, mud pumps, oil injection pumps, foam pump and water injection.	

We also supply alternative rotary head, and other accessories for above drill rig.

KNEBEL DRILLING A/S
INDUSTRIVEJ 20
DK-8550
RYOMGÅRD

TELEPHONE:
FAX:
GIRO:
E-mail

+45 86 39 45 00
+45 86 39 47 20
5 09 26 20
Knebeldrilling@knebeldrilling.dk

A/S REG. NR. 63479
SE DK 83089113
SE EXPORT DK 15 22 80 40